


NAiS

HE (High-function Economy) Type [1-Channel (Form A) Type] —With LED Display—

PhotoMOS RELAYS



- **Controls low-level analog signals**


PhotoMOS relays feature extremely low closed-circuit offset voltage to enable control of low level voltage signals or analog signals without distortion.

- **High sensitivity and low on resistance**

A stable relay that has a low on resistance of 16 Ω, no metal contacts, and the ability to control a maximum load current of 0.25 A with an input current of 5 mA.

- **Low-level off state leakage current**

In contrast to the SSR with its off state leakage current of several millamps, the PhotoMOS relay features a very small off state leakage current of only 100 pA even at a high load voltage of 400 V.



FEATURES

- Low on resistance and LED display
 - Same compact size of our conventional relays without LED display
- (W) 6.4×(D) 8.8×(H) 3.9 mm (W)
0.252×(D) 0.346×(H) 0.154 inch.

TYPICAL APPLICATIONS

- Telephones
- Measuring instruments
- Game machines
- High-speed inspection machines
- Industrial equipment

TYPES

Type	Output rating*		Part No.			Packing quantity		
			Through hole terminal	Surface-mount terminal				
	Load voltage	Load current	Tube packing style	Tape and reel packing style	Picked from the 1/2/3-pin side	Picked from the 4/5/6-pin side	Tube	Tape and reel
AC/DC type	400 V	150 mA	AQV254R	AQV254RA	AQV254RAX	AQV254RAZ	1 tube contains 50 pcs. 1 batch contains 500 pcs.	1,000 pcs

*Indicate the peak AC and DC values.

Note: For space reasons, the package type indicator "X" and "Z" are omitted from the seal.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item	Symbol	Type of connection	AQV254R(A)	Remarks
Input	LED forward current	I _F	25 mA	f = 100 Hz, Duty factor = 0.1%
	LED reverse voltage	V _R	3 V	
	Peak forward current	I _{FP}	60 mA	
	Power dissipation	P _{in}	90 mW	
Output	Load voltage (peak AC)	V _L	400 V	A connection: Peak AC, DC B, C connection: DC
	Continuous load current		A 0.15 A	
	B	0.18 A		
	C	0.25 A		
	Peak load current	I _{peak}	0.5 A	A connection: 100 ms (1 shot), V _L = DC
Power dissipation			360 mW	
Total power dissipation			410 mW	
I/O isolation voltage			1,500 V AC	
Temperature limits	Operating	T _{opr}	-40°C to +85°C -40°F to +185°F	Non-condensing at low temperatures
	Storage	T _{stg}	-40°C to +100°C -40°F to +212°F	


2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	Type of connection	AQV254R(A)	Remarks
Input	LED operate current	Typical	I_{Fon}	—	1.0 mA	$I_L = \text{Max.}$
		Maximum			3.0 mA	
	LED turn off current	Minimum	I_{Foff}	—	0.4 mA	$I_L = \text{Max.}$
		Typical			0.9 mA	
Output	LED dropout voltage	Typical	V_F	—	2.8 V	$I_F = 5 \text{ mA}$
		Maximum			3.5 V	
	On resistance	Typical	R_{on}	A	12.4 Ω	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$ Within 1 s on time
		Maximum			16 Ω	
		Typical	R_{on}	B	6.2 Ω	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$ Within 1 s on time
		Maximum			8 Ω	
Transfer characteristics	Typical	T_{on}	R_{on}	C	3.1 Ω	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$ Within 1 s on time
		Maximum			4 Ω	
	Off state leakage current	Maximum	I_{Leak}	—	1 μA	$I_F = 0$ $V_L = \text{Max.}$
	Switching speed	Turn on time*	T_{on}	—	0.8 ms	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$
		Turn off time*			2 ms	
	I/O capacitance	Typical	C_{iso}	—	0.05 ms	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$
		Maximum			0.2 ms	
	Initial I/O isolation resistance	Typical	R_{iso}	—	1.3 pF	$f = 1 \text{ MHz}$ $V_B = 0$
		Maximum			3 pF	
	Minimum		R_{iso}	—	1,000 MΩ	500 V DC

Note: Recommendable LED forward current $I_F = 5 \text{ mA}$.

*Turn on/Turn off time

For type of connection, see Page 444.




- For Dimensions, see Page 440.
- For Schematic and Wiring Diagrams, see Page 444.
- For Cautions for Use, see Page 449.

REFERENCE DATA

1. Input current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F;


Type of connection: A




2. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F;

Type of connection: A




3. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;
LED current: 5 mA;
Load voltage: 400 V (DC);
Continuous load current: 150 mA (DC)

AQV254R


4. Turn on time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: 400 V (DC); Continuous load current: 150 mA (DC)




5. Turn off time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: 400 V (DC); Continuous load current: 150 mA (DC)




6. LED operate vs. ambient temperature characteristics

Load voltage: 400 V (DC); Continuous load current: 150 mA (DC)




7. LED turn off current vs. ambient temperature characteristics

Load voltage: 400 V (DC); Continuous load current: 150 mA (DC)



8. LED dropout voltage vs. ambient temperature characteristics


LED current: 5 to 25 mA



9. Voltage vs. current characteristics of output at MOS portion


Measured portion: between terminals 4 and 6;

Ambient temperature: 25°C 77°F




10. Off state leakage current

Measured portion: between terminals 4 and 6; Ambient temperature: 25°C 77°F




11. LED forward current vs. turn on time characteristics

Measured portion: between terminals 4 and 6; Load voltage: 400 V (DC); Continuous load current: 150 mA (DC); Ambient temperature: 25°C 77°F



12. LED forward current vs. turn off time characteristics

Measured portion: between terminals 4 and 6; Load voltage: 400 V (DC); Continuous load current: 150 mA (DC); Ambient temperature: 25°C 77°F



13. Applied voltage vs. output capacitance characteristics

Measured portion: between terminals 4 and 6; Frequency: 1 MHz; Ambient temperature: 25°C 77°F

